NEBRASKA DEPARTMENT OF EDUCATION

RULE 91

REGULATIONS GOVERNING DRIVER QUALIFICATIONS AND OPERATIONAL PROCEDURES FOR PUPIL TRANSPORTATION VEHICLES

TITLE 92, NEBRASKA ADMINISTRATIVE CODE, CHAPTER 91

HEARING DRAFT OCTOBER 11, 2018



TITLE 92 - NEBRASKA DEPARTMENT OF EDUCATION

CHAPTER 91 - REGULATIONS GOVERNING DRIVER QUALIFICATIONS &

OPERATIONAL PROCEDURES FOR PUPIL TRANSPORTATION

VEHICLES

NUMERICAL TABLE OF CONTENTS

SUBJECT	STATUTORY <u>AUTHORITY</u>	CODE SECTION
General Information	79-318, 79-608	001
Definitions	79-318	002
Pupil Transportation Driver Qualification Criteria & Licensure	79-607, 79-608	003
Types of Permits and Licenses	79- 608	004
Operational Procedures	79-602, 79-608	005
Safe Pupil Transportation Vehicle Policy	79-318, 79-607	006

TITLE 92 - NEBRASKA DEPARTMENT OF EDUCATION CHAPTER 91 - REGULATIONS GOVERNING DRIVER QUALIFICATIONS & OPERATIONAL PROCEDURES FOR PUPIL TRANSPORTATION VEHICLES

ALPHABETICAL TABLE OF CONTENTS

SUBJECT	STATUTORY <u>AUTHORITY</u>	CODE SECTION
Definitions	79-318	002
Pupil Transportation Driver Qualification Criteria & Licensure	79-607, 79-608	003
General Information	79-318, 79-608	001
Operational Procedures	79-602, 79-608	005
Safe Pupil Transportation Vehicle Policy	79-318, 79-607	006
Types of Permits and Licenses	79-608	004

TITLE 92 - NEBRASKA DEPARTMENT OF EDUCATION

CHAPTER 91 - REGULATIONS GOVERNING DRIVER QUALIFICATIONS & OPERATIONAL PROCEDURES FOR PUPIL TRANSPORTATION

VEHICLES

Table of Contents for Appendices

<u>Appendix</u>	<u>Title</u>	<u>Page</u>
Α	Placement of Warning Flares/Reflectors	19
В	Emergency Evacuation Drill Procedures	20
С	Daily Pre-Trip Inspection Procedures	23
	Daily-Pre-Trip-Vehicle Inspection Form	28
Đ	Nebraska State Statute Section 13-1208 R.R.S (Use of School Buses)	29
E	Code of Federal Regulations 49 CFR 567.7 49 CFR 567.3	31 32
<u> </u>	Pre-Service Evaluation Form	33
G	Post Route Check of Vehicle	40

001 General Information

<u>001.01</u> <u>Statutory Authority.</u> This Chapter is adopted pursuant to Sections 79-318(132), and 79-607 of the Revised Statutes of Nebraska (R.R.S.).

"The State Board of Education shall: (13) With the advice of the Department of Motor Vehicles, adopt and promulgate rules and regulations containing reasonable standards, not inconsistent with existing statutes, governing: (a) The general design, equipment, color, operation, and maintenance of any vehicle with a manufacturer's rated seating capacity of eleven or more passengers used for the transportation of public, private, denominational, or parochial school students; and (b) the equipment, operation and maintenance of any vehicle with a capacity of ten or less passengers, used for the transportation of public, private, denominational, or parochial school students, when such vehicles are owned, operated, or owned and operated by any public, private, denominational, or parochial school or privately owned or operated under contract with any school in this state, except for vehicles owned by individuals operating a school which elects pursuant to section 79-1601 not to meet accreditation or approval requirements. Similar rules and regulations shall be adopted and promulgated for operators of such vehicles as provided in 79-607;"

And pursuant to Section 79-602 of the Revised Statutes of Nebraska (R.R.S.) which states in part:

"In addition to the inspection requirements prescribed in this section, the driver of each pupil transportation vehicle shall make daily inspections of such vehicle to ensure that all lights and equipment are fully operational or repaired before his or her daily route. Reports of such daily inspections shall be kept by the driver in the vehicle and filed weekly with the head mechanic or administrator in charge of the transportation system. If the inspection reveals any significant defect in the lights or equipment, the driver shall immediately report the defect to the head mechanic or administrator in charge of the transportation system."

And pursuant to Section 79-608 of the Revised Statutes of Nebraska (R.R.S.) which states in part:

"(1) Any person, before operating a school bus, including any school bus which transports students by direct contract with the students or their parents and not owned by or under contract with the school district or nonpublic school, shall submit himself or herself to (a) an examination, to be conducted by a driver's license examiner of the Department of Motor Vehicles, to determine his or her qualifications to operate such bus, and (b) an examination by a licensed physician to determine whether or not he or she meets the physical and mental standards established pursuant to Section 79-607 and shall furnish to the school board or board of education or the governing authority of a nonpublic school and the Director of Motor Vehicles a written report of each such examination on standard forms prescribed by

the State Department of Education, signed by the person conducting the same, showing he or she is qualified to operate a school bus and that he or she meets the physical and mental standards. If the Director of Motor Vehicles determines that the person is so qualified and meets such standards, the director shall issue to the person a special school bus operator's permit, which shall expire each year on the date of birth of the holder, in such form as the director prescribes. No contract shall be entered into until such permit has been received and exhibited to the school board or the governing authority of a nonpublic school. The holder of such permit shall have it on his or her person at all times while operating a school bus."

<u>001.02</u> <u>Scope and Application.</u> This Chapter governs: <u>the qualifications and requirements for drivers of pupil transportation vehicles in public and non-public schools, along with operational procedures for pupil transportation vehicles.</u>

O01.02A This regulation is not intended to include: (i) legally licensed operators of vehicles which operate under the jurisdiction of the United States Department of Transportation, State Patrol Motor Carrier Enforcement Division of Motor Carrier Services or Nebraska Public Service Commission when used for activity trips as described in subsection 002.02 of this Chapter; (ii) private motor vehicles used exclusively to carry members of the vehicle owner's household; (iii) small vehicles used for activity purposes only except as stated in subsection 003.01A; or (iv) the operation of small vehicles in emergency situations when approved by the school administrator or person designated by the local governing school board. The qualifications and requirements for drivers of pupil transportation vehicles in public and non-public schools.

<u>001.02B</u> The issuance of licenses and permits to drivers is subject to the regulations and/or procedures of the Nebraska Department of Motor Vehicles.

<u>001.02C</u> The operational procedures for pupil transportation vehicles.

<u>001.03</u> <u>Related Regulations.</u> An additional regulation promulgated by the Nebraska Department of Education dealing with pupil transportation vehicle drivers and equipment is Nebraska Department of Education is Chapter 92, Regulations Governing the Minimum Equipment Standards & Safety Inspection Criteria for Pupil Transportation Vehicles. In addition, Nebraska Department of Motor Vehicles has promulgated Title 247, Nebraska Administrative Code, Chapter 7, Rules and Regulations Pertaining to the Vision and Medical Requirements for Class A and B Licenses, Learner's and School Permits and School Bus Driver's Permits.

<u>001.04</u> <u>Penalty Provisions.</u> <u>According to Section 79-607 of the Revised Statutes of Nebraska</u> (R.R.S.): <u>provides that violations of traffic rules or regulations which relate to school bus transportation may result in a person being guilty of a Class V misdemeanor.</u>

"Any officer or employee of any school district who violates any of the traffic rules or regulations or fails to include obligations to comply with the traffic rules and regulations in any contract executed by him or her on behalf of a school district shall be guilty of a Class V misdemeanor and shall, upon conviction thereof, be subject to removal from office or employment. Any person operating a school bus under contract with a school district who fails to comply with any of such traffic rules and regulations shall be guilty of breach of contract, and such contract shall be canceled after notice and hearing by the responsible officers of such school district."

And to Sections 79-608(1) and 79-608(3) R.R.S:

"(1) No contract shall be entered into until such [operators] permit has been received and exhibited to the school board or the governing authority of a nonpublic school. (3) Any person violating this section shall be guilty of a Class V misdemeanor. His or her contract with the school district shall be canceled as provided in section 79-607."

<u>001.05</u> <u>Effective date and Implementation Date.</u> Regardless of the effective date of this Chapter, the implementation (operative) date will be ninety (90) days after its effective date. either January 1, 2019 or the effective date of this Chapter, whichever is later. Prior to that date, the provisions of 92 NAC 91 effective March 9, 2008 September 26, 2012 shall remain in effect.

002 Definitions

<u>002.01</u> Activity <u>Bus</u> shall means a motor vehicle with motive power, except a trailer, designed or modified by the manufacturer, distributor or dealer for carrying eleven (11) or more passengers, excluding the driver, which at any time would be used to carry school children and school personnel exclusively on a school activity trip from a given location to a second location without stopping to load or unload children or control traffic on public highways, provided that such transportation service is sponsored and approved by the local school governing board. This includes Multi-Function School Activity Bus as defined in 49 CFR 571.3. The preceding definition is not intended to and does not preclude the use of a school bus as an activity bus.

<u>002.02</u> Activity Trip shall means the transportation of children, pupils, and school personnel to and from a given location to a second or subsequent location or locations without stopping to load or unload the passengers on the public highways for the purpose of transporting the passengers to any activity or event sanctioned, authorized or sponsored by the school district or the local school's governing board.

<u>"Behind the Wheel" Training and Pre-Service Evaluation</u> shall means an orientation prescribed by the <u>Nebraska Department Commissioner</u> of Education and conducted by any driver holding a current school bus permit <u>or who is qualified to drive a pupil transportation vehicle</u>. The person conducting this orientation documents participation of the candidate by completing the Pre-Service Evaluation

Form (See Appendix F) and the School Transportation Maneuvers Road Test Examiner's Summary.

<u>Motor Coach Bus shall</u> means a vehicle not designed primarily for the transportation of school children to and from school and school related activities, but as a commercial motor vehicle for carrying eleven (11) or more passengers as a part of the operation of a common or contract carrier, as those terms are defined in Section 75-302 R.R.S., with a Gross Vehicle Weight of greater than 33,000 lbs., with a semi-monocoque/monocoque unitized body construction and which has front doors only high back seats, under-the-floor storage, and no rear emergency exit. and is designed to seat at least 32 passengers. For purposes of this Section, monocoque means a design where the skin or shell of the vehicle acts as a single unit with the supporting frame and semi-monocoque means a design where the skin or shell of the vehicle acts, to some extent, as a single unit with the supporting frame. Such buses are also commonly known as "motor coaches" or "over-the-road coaches."

<u>002.05</u> <u>Level I Instructional Course</u> <u>shall</u> means a minimum of an eleven (11) hour, <u>in-class</u>, instructional program for individuals who will be operating school buses <u>and a minimum of three (3) hour instructional program for drivers of small vehicles on routes. The content will be prescribed by the <u>Nebraska Department Commissioner</u> of Education, <u>and administered conducted</u> by an instructor approved by the <u>Nebraska Department of Education Commissioner</u>. The course and is valid for five (5) years.</u>

<u>O02.06</u> <u>Level I Waiver Examination</u> <u>shall</u> means an examination <u>administered by an instructor</u> approved by the <u>Nebraska Department Commissioner</u> of Education that may be taken prior to attending the Level I Instructional Course. <u>Achieving for which</u> a passing score on the waiver examination temporarily fulfills the Level I requirement for <u>all first time pupil transportation vehicle operator permit candidates.</u> <u>an individual to drive a pupil transportation vehicle for the first time.</u> <u>The applicant will be issued a Level I Waiver Card to carry while operating a pupil transportation vehicle or the applicant's information will be included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles. Sixty (60) days after being issued, the <u>Ww</u>aiver <u>Card</u> expires. <u>The applicant must complete the entire Level I training program before the "Level I Waiver Card" expires.</u></u>

<u>O02.07</u> <u>Level II Instructional Course</u> <u>shall</u> means a minimum of a three (3) hour <u>inclass</u> instructional program, <u>the content of which that</u> is prescribed by the <u>Nebraska Department Commissioner</u> of Education, <u>and administered conducted</u> by an instructor approved by the <u>Nebraska Department of Education Commissioner and is valid for five (5) years.</u>

<u>002.08</u> <u>Level II Waiver Examination</u> <u>shall</u> means an examination <u>administered by an instructor or an electronic method</u> approved by the <u>Nebraska Department Commissioner</u> of Education that may be taken prior to attending the Level II Instructional Course <u>for which</u>. <u>Achieving</u> a passing score on the waiver examination temporarily fulfills the Level II requirement for an individual to drive a pupil

transportation vehicle. The applicant will be issued a "Level II Waiver Card" to carry while operating a pupil transportation vehicle or the applicant's information will be included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles. Sixty (60) days after issuance, the "Level II Waiver Card" expires. The applicant must complete the entire Level II training program before the "Level II Waiver Card" expires. Instructional Course within sixty (60) days of passing the Level II Waiver Examination.

<u>002.09</u> <u>Students</u> shall means school students, pupils and children and will be used interchangeably throughout this Chapter.

<u>002.10</u> <u>School Bus</u> <u>shall</u> means a motor vehicle with motive power, except a trailer, designed or modified by the manufacturer, distributor or dealer for carrying eleven (11) or more passengers, excluding the driver, meeting or exceeding Nebraska Pupil Vehicle Minimum Standards (92 NAC 92); which at any time is used to carry school children and school personnel exclusively <u>that is sponsored and approved by the local school governing board</u>. <u>This School bus</u> includes an Activity Bus (as defined in this Chapter) and a Multi-Function School Activity Bus (MFSAB) as defined in 49 CFR 571.3 except where otherwise provided in 92 NAC 92. <u>Such transportation service must be sponsored and approved by the local school governing board. Vehicles that only carry school children along with other passengers as a part of the operation of a common carrier under the jurisdiction of the United States Department of Transportation, Nebraska Public Services Commission, Nebraska State Patrol Carrier Enforcement, or the Nebraska Department of Motor Vehicles Division of Motor Carrier Services are not included with the definition of school bus.</u>

<u>O02.11</u> <u>Small Vehicle</u> <u>shall be means</u> a motor vehicle with motive power, except a trailer, designed or modified by the manufacturer, distributor or dealer for carrying ten (10) or fewer passengers, excluding the driver, meeting or exceeding Nebraska Department of Education minimum standards for small vehicles which at any time would be used to carry <u>pupils</u> <u>students</u> exclusively <u>that</u> is <u>sponsored</u> and <u>approved</u> <u>by the local school governing board</u>. Such transportation service must be sponsored and <u>approved</u> by the local school governing board. If the seating capacity of the vehicle has been reduced to meet the definition of a small vehicle, the manufacturer, distributor, or dealer shall recertify the vehicle if required by 49 CFR 567.7. (See Appendix E.) The capacity of the vehicle shall be posted inside the vehicle in a conspicuous location. The preceding definition is not intended to include private motor vehicles used exclusively to carry members of the owner's household.

<u>002.11A</u> Vehicles that have an original manufacturer's vehicle type classification label under 49 CFR 567.4 of "bus" and that have an original manufacturer's designated seating capacity of 15 persons maximum (e.g. 15-passenger vans) shall not qualify as a small vehicle.

<u>002.12</u> <u>Pupil Transportation Vehicle</u> <u>shall</u> means any vehicle utilized to carry school children as sponsored and approved by the local school governing board and conforms to the Nebraska Department of Education definitions of pupil transportation vehicles listed <u>as School Bus, Activity Bus, Small Vehicle or Coach Bus in this Chapter.</u>

<u>002.13</u> <u>Pupil Transportation Vehicle <u>Driver Operator</u> <u>shall</u> means a driver of any pupil transportation vehicle, utilized to transport school children. <u>Driver qualifications</u> <u>and requirements are defined in this Chapter.</u></u>

<u>002.14</u> Route shall means a designated course regularly traveled by a pupil transportation vehicle to pick up students from home or pickup points and take them to school; or other locations related to a student's instructional program or to deliver students from school to their homes or designated drop-off points.

<u>002.15</u> <u>School Bus Permit</u> shall mean a permit that is required to be on the person of a vehicle operator driving a vehicle carrying school children. The operator of a small vehicle being used exclusively for extracurricular activities is not required to have a school bus permit.

003 Pupil Transportation Driver Qualification Criteria & Licensure

003.01 When a School Bus Permit is Required.

003.01A A school bus permit Pupil transportation vehicles used to transport one or more school children must be driven by individuals who have met the criteria as stated in this Chapter issued by the Nebraska Department of Motor Vehicles (see Section 004) is required for the driver of all vehicles used to transport one or more school children provided that whenever such transportation service is sponsored and approved by a local school's governing board. A permit is also required for those dDrivers employed by schools' independent contractors, and drivers independently contracted by a military base to transport one or more children to school must also meet this criteria to be qualified to drive a pupil transportation vehicle.

This regulation is not intended to include: legally licensed operators of "coach buses" which operate under the jurisdiction of the United States Department of Transportation, State Patrol Motor Carrier Enforcement Division of Motor Carrier Services or Nebraska Public Service Commission when used for activity trips as described in Section 002.02 of this Chapter; private motor vehicles used exclusively to carry members of the vehicle owner's household; small vehicles (cars and vans) used for activity purposes only; or the operation of small vehicles (cars and vans) in emergency situations, when approved by the school administrator or person designated by the governing school board.

<u>003.01A2</u> <u>Pupil transportation vehicle</u> <u>Ddrivers</u> of small vehicles on activity trips shall be provided <u>linstruction in emergency evacuation procedures, first aid, and other instruction applicable to the group of students being transported the following training by the appropriate local school, agency or contractor their employer prior to such transportation activity:</u>

<u>003.01A1a</u> Instruction in emergency evacuation procedures, first aid and other instruction applicable to the group of pupils being transported

<u>003.01B</u> Substitute pupil transportation vehicle <u>operators</u> drivers shall meet the same driver requirements and qualifications as a regular pupil transportation vehicle <u>operator</u> driver. A pupil transportation vehicle operator shall not have the authority to assign a substitute without the prior approval of any school administrator or person designated by the governing school board.

<u>003.01B1</u> A pupil transportation vehicle driver shall not have the authority to assign a substitute without the prior approval of a school administrator or person designated by the local governing school board.

<u>003.01C</u> The pupil transportation vehicle driver shall carry the following documentation while operating any pupil transportation vehicle (except those exempted under Section 002.14):

<u>003.01C1</u> A Nebraska Department of Motor Vehicles school bus permit (Section 79-608(1) R.R.S.)

<u>003.01C2</u> A current and valid Level I or II Instructional Course Card or be included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles.

<u>003.01C3</u> A current and valid United States Department of Transportation Medical Examiner's Certificate.

003.02 When a Commercial Driver's License is Required.

<u>003.02A</u> A commercial driver's license is required for the driver of a pupil transportation vehicle with a gross vehicle weight rating of twenty-six thousand one pounds (26,001) or more and/or designed to transport sixteen (16) or more passengers, including the driver. The holder of a commercial driver's license shall obtain any endorsements to operate a school bus required by the Motor Vehicles Operator's License Act (Section 60-462 et. seq. R.R.S.). An LPC-Learner's Permit for commercial vehicles is required prior to the commercial driver's license for the first school bus permit if operating a bus on a public roadway while preparing for the commercial driver's license exam pursuant to Section 60-4,141(2) R.R.S.

<u>003.02B</u> Substitute pupil transportation vehicle operators shall meet the same driver requirements and qualifications as a regular pupil transportation vehicle operator.

003.023 Requirements for to be a Pupil Transportation Vehicle Driver Qualification & Licensure

<u>003.023A</u> <u>Drivers Eligibility</u>. The following requirements shall be met <u>at all times</u> by the permit applicant prior to applying for an initial school bus permit, and for the renewal of a school bus permit required by the Nebraska Motor Vehicles Operator's License Act (Section 60-462 et. seq. R.R.S.). individuals to be a pupil transportation vehicle driver:

<u>003.023A1</u> The individual shall possess a valid Motor Vehicle operator's license required for the vehicle(s) that will be driven to transport students;

003.023A2 The individual shall be able to read and comprehend driving regulations and written test questions.

003.03A3 The school district, governing body, or employing agency shall verify or obtain a record at least annually of satisfactory driving as determined by the local school governing board policy. It is required that a copy of the individual's driving record be on file with the employing agency before employment as a pupil transportation vehicle operator, this includes drivers of small vehicles (cars and vans) for activity trips as described in Section 002.02 of this Chapter.

003.023A43 The individual shall be a minimum of 18 years of age; and

<u>003.023A54</u> The individual shall be of good moral character. The school district, governing body or employing agency shall obtain and keep on file a criminal history record of the driver applicants through the Nebraska State Patrol and local law enforcement agency before employment as a pupil transportation vehicle operator. Each driver's criminal history record shall be updated during the calendar year that coincides with the expiration of the individual's motor vehicle operator's license. This includes drivers of small vehicles (cars and vans), school buses, or activity buses whether for transporting pupils to and from school or for activity trips as described in Section 002.02 of this Chapter.

<u>003.03A5a</u> The school district, governing body or employing agency is not required to obtain a criminal history record for drivers who are also certificated Nebraska school administrators or teachers.

<u>003.02B</u> <u>Type of Vehicle Qualifications for Pupil Transportation Drivers.</u> The following categories of pupil transportation vehicles that drivers can be qualified to drive are:

<u>Category</u>	<u>Vehicle</u>	<u>Capacity –</u> <u>Not Including the Driver</u>	Minimum DMV License Required
<u>A</u>	Small Vehicle: Car or Van (Routes only)	1-10 passengers	Class O Operator's License
<u>B</u>	School Bus	Up to 14 passengers	Class O Operator's License
<u>C</u>	School Bus	15 or more passengers	Commercial Driver's License with Passenger and School Bus Endorsements

<u>O03.03B2C</u> <u>Initial Training</u> <u>Requirements for the First Permit to Qualify as a Pupil Transportation Driver.</u> <u>Prior to issuance of a school bus permit, wWhen an applicant individual</u> has never held <u>such a permit a school bus permit, or has never met the requirements to qualify to drive a pupil transportation vehicle, the following requirements shall be met:</u>

003.03B2C1 Successfully cComplete a "Behind the Wheel" training and preservice evaluation that. This evaluation is administered by a driver with a valid school bus permit or a driver who is qualified to drive a pupil transportation vehicle and holds an equal or higher vehicle qualification. Upon completion of the evaluation, the administering driver will issue a completed Pre-Service Evaluation Form (see Appendix FD) and School Transportation Maneuvers Road Test Examiner's Summary to the applicant individual. The applicant individual must hold an CLP-LPC-Learner's Permit for commercial vehicles before attempting to complete this training and evaluation pursuant to Sections 60-4,141 through 60-4,143 R.R.S., which is required if operating a bus on a public roadway. This evaluation shall be completed within six (6) months of completion of Level I Instructional Course and before a Level I Instructional Course Card is issued, or before confirmation of completion is forwarded to the Nebraska Department of Motor Vehicle for inclusion in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles.

<u>003.03B2C2</u> Successfully complete a Level I Instructional Course consisting of at least eleven (11) hours of class time. An applicant may waive the Level I requirement for sixty (60) days if the applicant receives at least the minimum score on the Level I waiver examination. Within sixty (60) days, the applicant must complete the Level I class. Upon completion of the Level I Instructional Course, the applicant shall receive a "Level I Instructional Course Card" issued by the Nebraska Department of Education or will be included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles. by receiving at least the minimum score on the Level I Instructional Course Exam.

O03.03B2C3 Pass a prescribed physical examination administered by a Certified Mmedical Eexaminer who is listed on the Federal Motor Carrier Safety Administration (FMCSA) National Registry, has been approved by the school district, governing body or employing agency. All physical examinations are to be conducted according to the Department of Transportation Federal Motor Carrier Safety Regulation Section 391.41 (49 CFR 391.41) and a record maintained as set forth in Department of Transportation Federal Motor Carriers Safety Regulation Section 391.43 (49 CFR 391.43). The This physical examination is valid for two (2) years ninety (90) days from the date of exam for Department of Motor Vehicles purposes. The individual shall provide the employer with a copy of the Medical Examiner's Certificate prior to operating any pupil transportation vehicle.

003.03B3a Each school district, or governing body shall have a valid Medical Examiner's Certificate for each driver it employs or contracts for on file. If the Medical Examiner's Certificate is valid for less than one (1) year, the school district, governing body, or employing agency shall require an updated valid Certificate prior to the expiration of the previous Certificate.

<u>003.03B3b</u> Any pupil transportation vehicle driver required to pass a physical exam who fails to maintain a valid Medical Examiner's Certificate with the school district, governing body, or employing agency shall be reported to the Department of Motor Vehicles and his or her permit shall be subject to recall.

<u>003.03B3c</u> Whenever it comes to the attention of a school official, member of the governing body of the school, employing agency, law enforcement officer, or medical examiner that the driver's Medical Examiner's Certificate has expired or becomes invalid, that person must provide notification to the Department of Motor Vehicles about the driver's invalid or expired medical certificate. The permit shall become subject to recall upon receipt of notification to the Department of Motor Vehicles.

<u>003.03B4</u> Pass the examination administered by the Nebraska Department of Motor Vehicles.

TITLE 92 CHAPTER 91

003.03C2D Requirements for the Renewal of a Permit for an Individual to Maintain Status as a Qualified Pupil Transportation Driver. A school bus permit shall be renewed annually. Prior to the issuance of a renewal permit, the following requirements shall be met individual shall:

<u>003.03C2D1</u> Meet the requirements The individual shall pass the prescribed annual physical examination on the form approved by the Department of Transportation as described in Ssubsection 003.032BC43. The individual shall provide a Medical Examiner's Certificate to the employing school, school's governing body or governing agency. The physical is valid for ninety (90) days from date of exam for Department of Motor Vehicles Purposes.

<u>003.03C2</u> The individual shall pass the annual vision test administered by the Department of Motor Vehicles. On the year that coincides with the expiration of the individual's motor vehicle operator's license, the individual shall pass a written exam skills test, and vision test.

O03.032C3D2 The individual shall hold a valid Level Instructional Course Card or the individual's information is included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles. Within five (5) years of completing a Level I Instructional Course and each subsequent five (5) year period, the driver shall successfully complete a Level II Instructional Course. administered by an instructor approved by the Nebraska Department of Education. This requirement may be waived for sixty (60) days if the applicant receives at least the minimum score on the Level II waiver examination. Upon completion of the Level II Instructional Course, a Level II Instructional Course Card will be issued by the Nebraska Department of Education or the individual's information will be included in the Interactive Driver's License Database maintained by the Nebraska Department of Motor Vehicles.

003.03C42D2a If more than five (5) years have passed since an individual has successfully completed a Level I or Level II Instructional Course, If a driver has either a Level I or Level II Instructional Course Card which has expired, the Level I Instructional Course shall be taken again.

003.03 Responsibilities of Employers of Pupil Transportation Drivers

<u>003.03A</u> Each employer shall have a valid Medical Examiner's Certificate for each driver it employs on file. If the Medical Examiner's Certificate is valid for less than two (2) years, the employer shall require an updated valid Certificate prior to the expiration of the previous Certificate.

<u>003.03B</u> When the employer becomes aware that a driver's Medical Examiner's Certificate is no longer valid, the employer will remove the driver from duties as a pupil transportation driver until a valid Medical Examiner's Certificate has been provided.

TITLE 92 CHAPTER 91

<u>003.03C</u> The employer shall annually obtain from the Nebraska Department of Motor Vehicles the driving record for every pupil transportation vehicle driver, and apply the satisfactory driving criteria, as determined by the local school governing board policy, before a pupil transportation vehicle driver may drive a pupil transportation vehicle.

<u>003.03D</u> The employer shall obtain a criminal history record that includes information from the Nebraska State Patrol for all individuals that are to be employed as pupil transportation vehicle drivers and keep a copy of that record on file.

<u>003.03D1</u> Each individuals' criminal history record shall be updated during the calendar year that coincides with the expiration of the individual's motor vehicle operator's license.

<u>003.03D2</u> The employer is not required to obtain a criminal history record for drivers who are also certificated Nebraska school administrators or teachers.

<u>003.03E</u> Employers shall annually provide a minimum of two (2) hours of inservice training for all pupil transportation vehicle drivers that, at a minimum, include emergency evacuations, loading/unloading, student management, vehicle inspections and the school's Safe Pupil Transportation Plan.

004 Types of Permits and Licenses.

<u>004.01</u> The Nebraska Department of Motor Vehicles shall test and issue the following school bus permits and commercial driver's licenses:

Permit Class	School Bus Permit Type	Capacity/Activity (Passengers only; count does not include the driver)	License Type Required
A	Small Vehicle/Van	1-10 passengers	Class O
₽	School Bus	Up to 14 passengers	Class O
E	School or Activity Bus/MFSAB	Up to 14 passengers/Activity only	Class O
Đ	School Bus	15 or more passengers	CDL
E	School or Activity Bus/MFSAB/Coach Bus	15 or more passengers/Activity only	CDL

<u>004.02</u> <u>School Bus Permit (Permit Class B, C, D, and E).</u> The applicant shall be given a school bus driver written examination and road proficiency test emphasizing the ability to perform all necessary safety functions during the process of pupil transportation route operations. The holder of a school bus permit may operate a school bus, activity bus, and small vehicle.

<u>004.03</u> <u>School Bus Permit Activity (Permit Class C and E).</u> The applicant shall be given a written examination and shall be required to demonstrate vehicle driving ability, excluding the process of controlling traffic and the loading and unloading of pupils on a public highway. The school bus (activity only) permit is not intended to include drivers operating vehicles under the United States Department of Transportation or Nebraska Public Service Commission regulations. The holder of school bus permit-activity may operate an activity bus and small vehicle.

<u>004.04</u> <u>School Bus Permit - Small Vehicle/Van (Permit Class A).</u> The applicant shall be given a written examination and driving proficiency test. The holder of a small vehicle operator's permit may operate a small vehicle only.

<u>004.05</u> <u>Commercial Driver's License (Permit Class D and E).</u> The applicant shall be subject to the regulations and testing procedures administered by the Department of Motor Vehicles. The holder of a Commercial Driver's License may drive a school/activity bus designed to seat 15 or more passengers, not including the driver.

<u>004.06</u> <u>Operator's License (License Class O).</u> The operator's license which authorizes the person to whom it is issued to operate on highways any motor vehicle except a commercial motor vehicle or motorcycle.

0045 Operational Procedures

O045.01 Pre-trip Vehicle Inspections. Designated pupil transportation personnel or designated personnel employed by a contractor which contracts for pupil transportation services with any school district or nonpublic school of the employer shall perform a pre-trip inspection prior to placing the vehicle in service once each day of operation at a minimum and shall promptly report in writing to the school administrator or person designated by the local school governing board any defects or deficiencies discovered that may affect the operational safety of the vehicle or result in its mechanical breakdown. The pre-trip inspection procedures require the conduction of both stationary and operating inspections. The daily inspection shall be conducted according to the procedures established by the Nebraska Department of Education. An example of a A Pre-Trip Vehicle Inspection Form appears in Appendix C. of this Chapter and is also available from Nebraska Department of Education, or its designee, in the publication, "Pupil Transportation Guide."

<u>004.01A</u> For purposes of this Section, a "trip" means the transportation from one predetermined destination to another with students on board. A new trip occurs whenever an hour or more expires before the next trip.

<u>0045.02</u> <u>Post-Trip Check.</u> <u>School bus Pupil transportation vehicle</u> drivers shall conduct an interior walk-through inspection for students that may remain on a <u>school school/activity/coach</u> bus, and a visual inspection for students that may remain in a <u>small vehicle</u>, at the end of each route or activity trip. <u>Drivers of small vehicles shall do a visual inspection for students that may remain on the vehicle at the end of each route or activity trip. An example of a Post-Trip Check of Vehicle Form has been included for schools to use in Appendix G.</u>

0045.03 Safe Stops for Loading and Unloading Children. No school bus shall stop to load or unload pupils unless there is at least four hundred (400) feet of clear vision in each direction of travel (Section 60-6,175(23) R.R.S.).

<u>0045.03A</u> When a school bus is (a) parked in a designated school bus loading area which is out of the flow of traffic and which is adjacent to a school site or (b) parked on a roadway which possesses more than one lane of traffic flowing in the same direction and which is adjacent to a school site, the bus driver shall engage only the hazard warning flasher lights when receiving or discharging pupils if a school bus loading area warning sign is displayed. Such signs shall not be directly attached to any school bus but shall be free standing and placed at the rear of a parked school bus or line of parked school buses. No school district shall utilize a school bus loading area warning sign unless such sign complies with the requirements of Section 60-6,176 R.R.S.÷

<u>005.03A1</u> Under Section 60-6,176 R.R.S., the Department of Roads, by rule and regulation, is to adopt and promulgate uniform standards for school bus loading area warning signs. Such standards shall include requirements for the size, material, construction, and required wording. No school district shall use a school bus loading area warning sign unless such sign complies with all rules and regulations adopted and promulgated by the Department of Roads. The cost of any sign shall be an obligation of the school district.

<u>0045.03B</u> The following procedure shall be <u>observed</u> <u>followed by the pupil</u> <u>transportation vehicle driver</u> when controlling traffic with a school bus during the process of loading and unloading:

0045.03B1 Use rearview mirror system to check all traffic.

<u>0045.03B2</u> Reduce the school bus speed with minimal brake usage and without greatly interrupting the flow of traffic.

0045.03C Activate the school bus flashing yellow warning signal lights:

0045.03C1 Not less than 500 feet or more than 1,000 feet from the bus stop in any area outside the corporate limits of any city or village; or

<u>0045.03C2</u> At least 300 feet and not more than 600 feet from the bus stop within the corporate limits of any city or village.

<u>0045.03D</u> During the stopping process, the pupil transportation vehicle shall allow sufficient area to the right of the bus so that children and other passengers may clear the bus safely.

<u>0045.03E</u> After the school bus has stopped, place the transmission in "Park". If there is no "Park" shift point, place the transmission in "Neutral" and set the parking brake at each stop. the pupil transportation vehicle driver shall:

<u>004.03E1</u> <u>Place the transmission in "Park", and if there is no "Park" shift point, place the transmission in "Neutral" and set the parking brake at each stop;</u>

<u>0045.03FE2</u> Check to see if traffic is able to stop, activate the alternating flashing red signal lamps, and extend stop arm-;

<u>0045.03GE3</u> Check to see if road is clear in both directions or that all traffic is stopped. When the road is clear and all traffic has stopped, open door to load and unload children and other passengers.

0045.03HE4 The operator of a school or activity bus shall require that when the children and other passengers have left the bus, they walk to a distance of approximately twelve (12) feet in front of the bus before crossing the roadway.

<u>0045.03IE5</u> When children and other passengers are safely across the road, or on their way home, <u>the pupil transportation vehicle driver shall close the door, ensure all passengers are seated,</u> retract stop arm, turn off alternately flashing warning lights, check the traffic and proceed. When loading, do not put bus in motion until door is closed and children and other passengers are seated. All passengers shall remain seated while the bus is in motion.

<u>0045.04</u> Railroad Crossing Procedure. The following sequence of actions apply to all <u>drivers of</u> school buses, activity buses, and Multi-Function School Activity Buses (MFSAB), either loaded or unloaded, during the process of approaching and crossing railroad tracks except at any such crossing where a police officer or a traffic control flagman (railroad employee) directs traffic to proceed.

<u>0045.04A</u> Approach the tracks with caution and decelerate the vehicle-:

<u>0045.04B</u> Activate the hazard warning flasher lights at a distance of not less than 200 feet from the nearest railroad track-;

<u>0045.04C</u> Stop the school bus within 50 feet, but not less than 15 feet from the nearest rail. Pplace the transmission in "Park. and lift there is no "Park" shift point, place in "Neutral" and press down on the service brake or set the parking brakes.

<u>0045.04D</u> Command the cooperation of passengers in an effort to provide maximum quietness.; <u>Demand cooperation if necessary.</u>

<u>0045.04E</u> After quietness aboard the stopped school bus has been achieved, open the service door and driver's window, listen and look in both directions along such track for any approaching train and for signals indicating the approach of a train-: If no train is approaching, proceed in a gear low enough to permit crossing the tracks without having to shift gears. Vehicles with automatic transmissions should put the transmission in the drive gear. The door must be closed by the time the rear bumper of the bus is clear of the track.

<u>004.04F</u> If no train is approaching, proceed in a gear low enough to permit crossing the tracks without having to shift gears (vehicles with automatic transmissions should put the transmission in the drive gear);

<u>0045.04F1</u> When two (2) or more tracks are to be crossed, do not stop unnecessarily a second time unless the rear bumper of the school bus is completely clear of the first track and has at least 15 feet clearance in front and at least 15 feet clearance from the track to the rear.

0045.04G Railroad tracks shall not be crossed unless absolutely certain there would be at least 15 feet of clearance from the rear bumper of the school bus to the nearest rail should the bus need to stop after crossing the railroad tracks-; and

<u>0045.04H</u> Deactivate warning hazard lights after the bus completely crosses the railroad tracks.

<u>0045.05</u> Emergency Evacuation Drill Procedure. At least twice during each school year, each pupil who is transported in a school bus shall be instructed in safe riding practices and participate in emergency evacuation drills <u>conducted by a pupil transportation vehicle driver who is qualified to operate a school bus.</u> The emergency evacuation drill procedure <u>should will</u> be conducted according to the <u>guidelines established by the Nebraska Department of Education (see Appendix B)</u>. The chief administrative officer or chairperson of the board of education representing a public school district or the chief administrative officer or chairperson of the governing authority representing any nonpublic school shall annually certify, <u>by</u> a <u>written</u> verification statement, to the Department of Education that the evacuation drills required pursuant to this <u>sS</u>ection have been conducted. Such verification statement shall be sent to the Department of Education no later than June 30.

0045.06 Accident Procedures and Prevention

<u>0045.06A</u> The following procedures shall be observed by a pupil transportation vehicle driver in the case of an accident involving a pupil transportation vehicle.

<u>0045.06A1</u> Stop the vehicle immediately-;

Remain at the scene of the accident. There is a severe penalty for a person convicted of leaving the scene of an accident in which they are involved. and Rrender any person injured in the accident reasonable assistance to any person injured in the accident;

0045.06A3 Make certain all pupils are in a safe place away from traffic and that they pupils are not permitted to leave the assigned area without permission.;

<u>0045.06A4</u> Notify the law enforcement agency immediately. As necessary, and inform the school administrator and request medical assistance.

<u>0045.06A5</u> <u>Obtain</u> <u>Information such as the</u> names, license numbers, registration numbers, location, time, road and weather conditions shall be obtained and that are accurately written down;

<u>0045.06A6</u> Three flares or reflectors shall be sSet three flares or reflectors to warn traffic₁ as follows:

<u>0045.06A6a</u> On the traffic side of the vehicle, within ten (10) feet of the rear corner to mark the location of the vehicle.

<u>0045.06A6b</u> On the shoulder of the road or in the lane the vehicle is stopped in, about 100 feet behind and ahead of the vehicle. (See Appendix A, Figure 1)

<u>0045.06A6c</u> Back beyond any hill, curve, or other obstruction that prevents other drivers from seeing the vehicle within 500 feet. (See Appendix A, Figure 2)

<u>0045.06A6d</u> If the vehicle must stop on or by a one-way, or divided highway, place warning devices flares or reflectors 10 feet, 100 feet, and 200 feet toward the approaching traffic.

<u>0045.06A7</u> Provisions shall be made for transporting pupils to their homes or to school as determined by local school policy.

<u>0045.06A8</u> The <u>operator driver</u> of any pupil transportation vehicle, which is in any manner involved in an accident within the state, in which any person is killed or injured, or in which damage to an apparent extent in excess of \$1,000.00 is sustained to the property of any one person, including such <u>operator driver</u> shall within ten (10) days report the matter in writing on prescribed forms to the Nebraska Department of Motor Vehicles.

<u>0045.06B</u> <u>Procedures for Other Accidents.</u> When a pupil transportation vehicle operator driver approaches a scene of an accident in which the pupil transportation vehicle is not involved and no other assistance is available, the vehicle operator driver shall stop, put on four (4)-way flashers to warn approaching traffic and determine the necessity of being of assistance, provide reasonable assistance and thereafter immediately continue on the route schedule.

0045.07 Additional Pupil Transportation Vehicle Operating Regulations

<u>0045.07A</u> <u>Speed Limits.</u> The maximum pupil transportation vehicle speed limit shall be as posted or as otherwise provided by applicable laws or ordinances; however, speed should be governed by reasonable individual judgment and existing operating conditions.

<u>0045.07B</u> <u>Convoy Distance.</u> A pupil transportation vehicle shall not follow another vehicle within 475 feet when traveling outside the corporate limits of a town or city. The preceding is not intended to prevent a pupil transportation vehicle from passing another motor vehicle.

<u>0045.07C</u> <u>Tobacco Products.</u> Smoking and/or the use of any tobacco product in a pupil transportation vehicle shall be prohibited at all times.

<u>0045.07D</u> <u>Backing.</u> The <u>operator</u> <u>driver</u> of a school, activity, or coach bus owned and operated by a school shall not drive backwards on the school grounds unless the rear of the bus is observed and directed by a second responsible person. The <u>operator driver</u> of any pupil transportation vehicle shall not back such vehicle on any roadway unless such movement can be made with safety and without interfering with other traffic.

<u>0045.07E</u> <u>Towing.</u> Pupil transportation vehicles shall not be operated with a trailer or other vehicle attached while children are being transported.

<u>0045.07F</u> <u>Occupant Protection Systems.</u> The operators of pupil transportation vehicles <u>driver</u> shall be required to wear lap/<u>shoulder</u> belts whenever the vehicle is in motion. When occupant protection systems/<u>lap belts</u> are provided in the pupil transportation vehicle, passengers shall wear the occupant protection system. Children <u>up to the age of eight (8) years of age</u> shall use <u>Federally-approved</u> child passenger restraint systems as required by Section 60-6,267 R.R.S.

<u>0045.07G</u> Hourly Driving Limitation. It shall be unlawful for any person operating a pupil transportation vehicle to be or remain on duty for a longer period than sixteen (16) consecutive hours. When any person operating a pupil transportation vehicle shall have been continuously on duty for sixteen (16) consecutive hours, he or she shall be relieved and not be permitted or required to again go on duty without having at least ten (10) consecutive hours off duty, and no such operator driver, who has been on duty sixteen (16) hours in the aggregate in any twenty-

four (24) hour period, shall be required or permitted to continue or again go on duty without having had at least eight (8) consecutive hours off duty.

<u>0045.07G1</u> For purposes of this Section, "on duty" means time spent doing any of the following: driving, loading, unloading, or supervising or assisting in loading or unloading persons or property from or into vehicles, or repairing, inspecting or otherwise attending to a vehicle or its passengers.

<u>0045.07G2</u> When transportation of pupils is subject to the hourly driving limitation of the Federal Motor Carrier Safety Regulations (49 CFR Part 395), then such requirements shall govern.

<u>0045.07H</u> <u>Seating.</u> Seating shall be provided that will permit each occupant to sit in a seat as intended by the manufacturer. Neither the manufacturer's rated seating capacity nor the manufacturer's gross vehicle weight (GVW) shall be exceeded at any time the pupil transportation vehicle is in motion. In addition, the aisle and exit and entry areas shall be clear and unobstructed while the pupil transportation vehicle is in motion. Routing and seating plans shall be coordinated so as to eliminate standees when a school vehicle is in motion. There shall be no auxiliary seating accommodations such as temporary or folding jump seats in pupil transportation vehicles. If permanent seats are removed or added to a pupil transportation vehicle, such installation shall be completed by the dealer or manufacturer.

<u>0045.07I</u> <u>Use of Strobe Light.</u> The white flashing strobe light shall be used only in adverse weather conditions, when the pupil transportation vehicle is in distress or to enhance the visibility of the pupil transportation vehicle when barriers inhibit such visibility.

<u>0045.07J</u> <u>Use of Headlights.</u> Pupil transportation vehicles shall operate with headlights on at all times.

<u>0045.07K</u> <u>Small Vehicles Used on Routes.</u> When a small vehicle is used to transport students on a route, the driver shall pull off the road into a driveway, parking lot, or other appropriate safe location prior to loading and unloading students.

<u>0045.07L</u> <u>Use of Handheld Wireless Communication Device.</u> Drivers shall not use a handheld wireless communication device to read written communication, type written communication, or send written communication while operating pupil transportation vehicles. If the use of a handheld wireless communication device, is necessary, whether for written or verbal communication, is necessary, the driver shall pull the pupil transportation vehicle onto the shoulder off of the road or parking lots before using this device. (This does not preclude the use of a two-way communication device required by 92 NAC 92-Ssubsection 005.131.)

<u>0045.07M</u> <u>Leaving Pupil Transportation Vehicle with Passengers on Board.</u> Unless a running engine is required to operate a power lift or ramp (see 92 NAC 92-007.07), drivers of pupil transportation vehicles shall not leave a pupil transportation vehicle when passengers are on board unless the vehicle is parked in a safe location, the engine is in the off position, the keys have been removed and in the possession of the driver.

00<u>5</u>6 Safe Pupil Transportation

<u>0056.01</u> <u>Transportation of Unsafe Items.</u> Pupil transportation vehicles shall not transport any items, animals, materials, weapons or look-a-like weapons, <u>explosive</u> <u>devices or bomb-related materials</u> or equipment which in any way would endanger the lives, health, or safety of the children, and other passengers and driver.

<u>0056.01A</u> Look-a-like weapons associated with a school sponsored or approved activity may be transported with written permission of an administrator of the school district. <u>If possible, these items should be secured and not visible or accessible to students while on the pupil transportation vehicle.</u>

<u>0056.01B</u> Any item or items that would break or could produce injury if tossed about the inside of pupil transportation vehicle when involved in an accident shall be secured.

<u>0056.02</u> <u>Safe Pupil Transportation Plan</u>. Each school district providing pupil transportation shall have a safe pupil transportation plan.

<u>0056.02A</u> The Plan may be incorporated or addressed in a school's safety and security plan adopted pursuant to 92 NAC 10 or can be a separate plan. At minimum, the plan shall address:

0056.02A1 Weapons.

<u>0056.02A2</u> Pupil behavior that is in violation of Student Conduct Standards established by Section 79-262(1) R.R.S or similar rules.

0056.02A3 Terroristic threats.

0056.02A4 Severe weather.

<u>005</u><u>6.02A5</u> Hazardous materials <u>and unattended items on or near pupil transportation vehicle.</u>

0056.02A6 Medical emergencies.

<u>0056.02A7</u> Driver/passenger procedures in the event of mechanical breakdowns of the vehicle.

<u>0056.02A8</u> Driver procedures in the event that the drop-off location is uncertain or appears unsafe to leave students.


<u>005.02A9</u> <u>Functional capacity of a pupil transportation driver and a process to confirm a driver's ability to conduct daily tasks and emergency evacuations.</u>


<u>0056.02B</u> <u>Documentation under Safe Pupil Transportation Plan.</u> Each school district providing pupil transportation shall develop a procedure that requires pupil transportation vehicle operators <u>drivers</u> to document and submit to designated school authorities the occurrence of any events covered by the Safe Pupil Transportation Plan adopted under <u>Ssubsection 0056.02</u>, that involved the pupil transportation vehicle operated by the driver, or any pupils transported in it.

<u>0056.03</u> <u>Authorized Passengers</u>. No one except school personnel, supervisory personnel, monitoring personnel and pupils assigned to a school bus for a particular route schedule or for an activity trip as defined in 92 NAC 91- <u>Ssubsection</u> 002.02 may ride in such vehicles.

<u>0056.03A</u> This <u>sS</u>ection shall not limit the types of passengers that may otherwise be transported in a school bus when used for other than to or from school purposes under Section 13-1208 R.R.S., Section 60-6,175(<u>67</u>) R.R.S., or as otherwise authorized. <u>See Appendix D.</u>

APPENDIX A - PLACEMENT OF WARNING FLARES/REFLECTORS





APPENDIX B - EMERGENCY EVACUATION DRILL PROCEDURES

In a school bus accident or emergency situation, the school bus driver must use his/her best judgment to decide what action shall be taken. The primary responsibility is pupil safety. In an emergency it may be necessary that the bus be evacuated. This procedure requires a definite plan followed by periodic practice in emergency evacuation drills.

The following procedures apply to school buses. Local policies must be developed to include instructing emergency equipment and evacuation procedures for students who ride small vehicles.

1. Reasons for Emergency Evacuation of School Buses

- A. Fire or danger of fire If any portion of a school bus is on fire, it shall be stopped and evacuated immediately. Passengers shall move to a point 100 feet or more upwind from the bus and remain there until the bus driver has determined that no danger remains. If a school bus is unable to move and is close to existing fire or highly combustible materials, the "danger of fire" shall be assumed and all passengers evacuated.
- B. Unsafe Location In the event that a school bus is stopped in an unsafe location and is unable to proceed, the driver must determine immediately if it is safer for passengers to remain on the bus or to evacuate.
- C. Driver must evacuate a school bus if its final stopping position:
 - 1. is in the path of any train, or on or closely adjacent to any railroad tracks;
 - 2. could change and increase the danger. For example, if a bus were to come to rest near a body of water or precipice where it could slide into the water or over a cliff, it must be evacuated;
 - 3. is such that there is danger of collision. Under normal traffic conditions, the bus should be visible for a distance of 300 feet or more. A position over a hill or around a curve where such visibility does not exist should be considered reason for evacuation.

2. Important Factors in School Bus Evacuation

- A. The safety of the pupils is of utmost importance and must be given first consideration. During an evacuation, pupils should be led to a safe place at least 100 feet off the road in the direction of oncoming traffic. If there is a risk from spilled hazardous materials, lead the pupils upwind of the bus at least 300 feet.
- B. Prior to evacuation, place the transmission in park (neutral), activate the hazard warning light, set the emergency brakes, turn the ignition off, and remove the ignition key.
- C. The driver shall stay in the bus during evacuation to guarantee smoothness of evacuation procedures.

APPENDIX B - EMERGENCY EVACUATION DRILL PROCEDURES

- D. Evacuations shall be conducted with "deliberate speed." A time interval of $1\frac{1}{2}$ to 2 seconds per passenger has proven to be the safest and most efficient.
- E. To insure a safe exit, passengers must have their hands free. They shall leave lunch boxes, books, and other personal belongings on the bus.
- F. Passengers selected and trained in advance shall be assigned to serve as:
 - 1. Leaders will lead passengers to safety from each door utilized for evacuation. (Passengers shall be directed to a safe point at least 100 feet from the bus and remain there until given further directions.)
 - 2. Helpers two pupils shall be stationed to aid passengers as they leave the bus through the rear emergency exit.

3. Common Types of School Bus Emergency Evacuation.

- A. Evacuations utilizing the front or service door shall be conducted using the same techniques as a routine unloading. The driver will choose whether to evacuate the bus one side at a time or on a staggered seat basis.
- B. Evacuations utilizing only the rear exit door have some distinctive features.
 - 1. The bus driver shall walk back through the bus to the rear exit and direct the pre-assigned leader and helpers to take their positions.
 - 2. The leader will open the rear emergency door, exit, and stand clear, ready to lead exiting passengers to a safe location set by the driver.
 - The helpers will exit and take their position, one on each side of the rear emergency exit to assist passengers in exiting the bus in a safe and orderly manner.
 - 4. Passengers shall remain in their seats until directed by the driver to leave the bus. The driver may choose whether to evacuate the bus one side at a time or on a staggered seat basis.
 - 5. The driver shall advise all passengers to have their hands free and coats buttoned. Each passenger shall be two steps away from the bus before the next person exits. Taller passengers would be reminded to duck their heads in order to exit safely.
- C. Evacuations utilizing roof hatches, side emergency doors, and side/rear emergency windows. Should the bus be on its side, utilize the roof hatches and side door. The side door is located on the left side, the street side, of the bus. Use caution exiting, as belongings will be tossed around and might be a hazard underfoot. Evacuation procedures are the same as if utilizing the 5 step rear door exit evacuation. Follow the instructions for opening the side/rear window emergency exits. Instructions are displayed on the door and below the window.

APPENDIX B - EMERGENCY EVACUATION DRILL PROCEDURES

D. Evacuation of pupils with disabilities - Each bus route shall have its own written emergency evacuation plan.

E. School Bus Pupil Representatives

- The school bus driver is responsible for the safety of pupils. However, in an emergency a driver might be incapacitated, unable to direct evacuation. Therefore, school bus representatives (school safety patrol members or appointed pupil) should be selected, trained and prepared to direct the evacuation.
- 2. School bus representatives should be: a) mature pupil maturity is more important than age; b) good citizens a desire to serve is most important; c) on the bus for the entire route. Choosing pupils who live near the end of the route might be helpful. They must also have written parental permission in advance.
- 3. Training programs shall prepare pupils, school bus representatives to: a) turn off ignition switches; b) set emergency brakes; c) summon help when and where needed (instructions and telephone numbers shall be available on buses); d) use windows for evacuation in emergencies; e) set flags and reflectors or reflective triangles; f) open and close service and emergency exit doors; g) direct school bus evacuations; h) perform other duties as directed by the driver.

F. School Bus Evacuation Drills

- 1. All pupils who are transported in a school bus shall be given an opportunity to participate in evacuation drills.
- 2. All pupils shall be instructed in school bus passenger safety and procedures for emergency evacuation prior to participation in evacuation drills.
- 3. Drills should be held in restricted off-street areas and not on bus routes.
- 4. All types of emergency evacuations should be practiced with emphasis on utilizing the rear emergency exit.
- 5. Section IV, subsection C-2 of Standard 17 of the Federal Highway Safety Act of 1966 and Section 79-609(2)(a) R.R.S. states: "At least twice during each school year, each pupil who is transported in a school vehicle shall be instructed in safe riding practices and participate in emergency evacuation drills."

The school bus driver must perform a daily pre-trip inspection of the school bus and equipment before transporting pupils. This pre-trip inspection consists of the following:

- a. Bus exterior
- b. Bus interior
- c. Operating Daily Road Check

The driver of a small vehicle must perform a daily pre-trip inspection before the vehicle is used for transporting pupils.

Before starting the engine, drivers should conduct an interior and exterior walk-around, visually checking behind doors, accessible panels, under seats, undercarriage, etc., for suspicious items. If a suspicious item is found, the driver should clear the immediate area and notify authorities, as determined by the local school officials.

CARE & INSPECTION

Exterior Inspection or the "Daily pre-trip Walk-Around"

Before conducting the daily pre-trip walk-around, start the engine and allow the vehicle to warm-up. Do not leave the vehicle while it is warming up. Set the parking brake and put the transmission in neutral. Then get out and inspect the vehicle thoroughly – top to bottom and end to end. Walk completely around it, alert to faulty equipment. Carry supplies to clean the lights, mirrors, signs, and windows. When the vehicle lights and signs are not visible because of dirt, other motorists can come to close to the vehicle before reacting. If the headlights, mirrors, or windows are dirty, reaction time is reduced due to poor visibility.

Listed below is each piece of equipment to be inspected for proper working order and warnings, which point to potential problems.

[Pre-trip inspection for small vehicles consists of inspecting the items below which have been indicated by an asterick (*).]

- Lights* Check all lights applicable to the vehicle: back-up lights, brake lights, directional signals, hazard flashers, headlights, lighted school bus sign, reflectors, running lights, stop arm lights, taillights, and warning lights. Any lights or reflectors exhibiting such problems as inconsistent flashing, cracks, or other damage, should be reported in writing and repaired.
- Mirror* Mirrors should be aimed and tightly adjusted. Make certain you have a safe view.
- Windows* All windows, especially the windshield and rear window, should be clear of dirt, ice, road film, and snow that can cause glare or impair visibility. Do not clear just a "peephole." Inspect windows for cracks and report any problems to the administration.

- **Emergency Rear Door** Check to see that it opens easily from the outside. The emergency door-warning buzzer should sound when the door is opened and the ignition key is on. This door must always be ready for emergencies, yet tightly sealed when closed to prevent possible entrance of carbon monoxide fumes.
- Exhaust System* Carbon monoxide poisoning occurs the most frequently when a vehicle is standing still or is in an enclosed space with the engine running. Look for visible exhaust and listen for excessive noise and vibration. Check for leaks in the exhaust system and holes in the body of the vehicle. Leaks should immediately be reported and repaired. The exhaust system should also be checked for sagging tailpipes (exhaust pipes) and mufflers.
- Fluid Leaks* Examine inner wheels and tires and the area under the vehicle for wetness. Leaks can be engine oil, coolant, fuel, rear axle fluid, or grease, as well as brakes, clutch, or transmission fluid. Leaks should immediately be reported and repaired.
- **Tires *-** Check the tires and see to if they are under inflated, flat, excessively worn or damaged. Don't drive the vehicle unless the tires are in good shape. One flat rear tire can place a dangerous weight on the companion tire of a dual set.
- Wheels* Look for loose or missing nuts, excessive corrosion, cracks or other damage. Don't drive with a damaged wheel or with loose wheel nuts.
- **Under the Hood*** Before starting the engine for the daily walk-around, you should check the coolant and/or antifreeze and oil to make sure they are at the proper level. Also, look for cracked, loose, or worn drive belts, hoses, and hose clamps.

Interior Inspection

After the exterior inspection is complete, the vehicle should be checked thoroughly on the inside. All driver's instruments and controls must be functioning properly. All of the following items should be checked before operating the vehicle.

- **Lights*** Check the panel light and the interior dome lights. They should be clean and work properly.
- **Mirrors*** They should be adjusted, aimed and cleaned so your visibility is unobstructed.
- Windows* These should be cleaned from the inside as well as the outside, for total visibility, especially the windshield and rear window. Check for cracks in the windows and report any problems to the administration.
- **Defroster, Fan and Heater*** The vents should be unobstructed; i.e., do not cover them with coats, books, papers, etc., to insure that air moves through properly.

- **Driver's Seat and Seat Belts*** These should be adjusted so that the driver's feet reach the pedals, the doors, mirrors, and windows are in comfortable viewing distance, and the steering wheel is easily grasped without stretching or reaching. Seat belts for all passengers (including the driver) shall be in working order.
- **Emergency Door and Buzzer** The door should be tightly sealed from the inside, but ready for emergency use. The buzzer should sound when the door is opened.
- Emergency Equipment* All emergency equipment should be easily accessible, yet out of the pupil's reach. Emergency equipment consists of the first aid kit, fire extinguisher, and reflectors. The fire extinguisher should be undamaged and properly stored. Replace cracked or broken hoses, keep nozzles unobstructed and make sure locking pins and sealing wires are in place. Periodically, shake the fire extinguisher to loosen the powder.
- Horn* It should sound clearly without the horn or horn button sticking.
- Stop Arm Control and Service Door Control Check to see that the controls coordinate with the actions of the stop arm and door. If there is a problem, it should be reported and repaired.

*The windshield wipers and washers, the steering wheel, and neutral safety switch should also be checked to make sure they are in proper working order.

The following equipment of the Interior Inspection should be checked with the engine running:

- Air Pressure or Vacuum Gauge This gauge indicates the proper capacity of pressure to operate the brakes. Do not operate the vehicle until the pressure reaches the proper capacity. Loss of pressure indicates a leak in the system.
- **Voltmeter Gauge** The voltmeter gauge indicates the voltage of the electrical charging system. This meter should show about 14 volts with the engine running. If it shows a higher or lower voltage, the vehicle should be checked.
- Brake Pedal and Warning Light If the light comes on during a hard brake application, in a vehicle equipped with a dual brake system, it indicates that at least one of the brake systems is not working properly.
- Fuel Gauge* It should indicate a safe margin of fuel for operating, never less than ¼ full.
- Oil Pressure Gauge* The oil pressure gauge indicates the proper oil pressure. If it does not, the engine should be turned off. Learn what the proper oil pressure is for the vehicle.
- Water Temperature Gauge* The water temperature gauge indicates the temperature of the coolant in the engine. It should read COOL or WARM. If it reads HOT, the engine should immediately be turned off and the problem reported.

Be sure to check the passenger compartment; inspecting seats and windows, making sure there are no potential missiles (such as lunch boxes, toys, or school books) laying on the seats or floor.

Operating - Daily Road Check

The operating inspection is performed while the vehicle is being driven. A daily road check, both before and after loading the pupils, allows the driver to evaluate the working condition of that equipment which can only be inspected while the vehicle is in motion.

A driver should be constantly aware of the weight and motion of the passengers and how the vehicle is affected (as in pick-up characteristics, the tendency to drift, how the vehicle handles on curves, etc.) by always monitoring how the engine performs under load. The operating inspection consists of checking the following:

- Brakes *- Do not wait until the vehicle is on the road to test the brakes. They can be tested in the yard at the bus garage. Moving at a low speed, come to a complete stop. The vehicle should stop in a straight line without pulling to one side, skidding, or swerving. The brakes should not grab, lock, or make excessive noise such as squeaking or squealing. The brake pedal should not feel grabby, over sensitive, or spongy. When the brakes are not in use, watch for dragging which causes the vehicle to pull to one side.
- Clutch (if applicable) When changing gears, the driver should control the speed of the engine so the shift can be completed easily and smoothly without jerking or slipping. Careless shifting wears out the clutch and reduces its service life. When the shift is completed, remove foot from the clutch-do not "ride" the clutch. When the pedal is released, the clutch should have some "free play." Watch for dragging, grabbing, or lack of free play on the pedal. Listen for unusual sounds. If you smell an odor like burning rubber, the vehicle should immediately be stopped.
- Emergency Parking Brake To test both air and mechanical brakes with a manual transmission, slowly engage the clutch while the parking brake is on. If the vehicle moves easily, the parking brake is not holding and should immediately be reported. With air brake systems, the parking brake will remain applied if there is partial or complete air loss in the service brakes. Release the parking brake when the vehicle is in motion. Driving with the parking brake on is a frequent cause of failure of the emergency brake.
- **Engine*** Do not race the engine when it is cold. Increase the engine's speed slowly so that all the parts can be lubricated. Do not exceed the maximum rpm. Listen for unusual sounds such as backfire, light tapping, occasional misfire, piston slap, rapid hammering, or whistling. Be alert to slow engine warm-up, lack or normal response, vibrations of the chassis, or failure of warm engine to start.

- **Steering*** The steering should be easy to handle, precise, responsive, and steady in turns and over rough roads. Power steering should be exceptionally quiet. The steering should not have excessive "play," jerking, "kickback" or rattles.
- **Suspension*** Improper suspension can cause "bottoming," excessive bounce, swaying and weaving on curves or rough roads, or one end of the vehicle to sag. Check for broken springs or faulty shock absorbers.
- Transmission* With the transmission in a moving gear, the vehicle should move smoothly in response to depressing the accelerator. An automatic or manual transmission should slip into gear and have easy and smooth gear changes throughout the shifting range. Do not exceed the manufacturer's recommended speed for each specific gear (rpm). Exceeding speed recommendations could damage the transmission or reduce its service life. Any metallic or unusual sounds or shifting difficulty should be reported immediately.

Continue to check all equipment throughout the day being alert to warning signs which will indicate potential problems. Be aware that the condition of the vehicle changes during the day.

At the end of the operating period check the passenger compartment for remaining passengers, lost articles such as books, lunch boxes, clothing, or toys. Inspect the seats for damaged upholstery and the window for cracks or breaks. Clean the vehicle, sweeping the floor, washing the seats, windows, and exterior.

APPENDIX C - DAILY PRE-TRIP VEHICLE INSPECTION PROCEDURES This document is provided as an example of a pre-trip/Daily Inspection Form — schools should and can be adapted to suit the district

ols should and can be adapted to suit the district individual needs. Completed

Daily <u>Pre-Tr</u>	ip Vehicle Inspection	n Forn		in your init pections hav			ch day to c	onfirm the
Vehicle No.		Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Other
Visual Check of Ve	ehicle Interior and Exterior							
for Suspicious Iter								
ioi odopioiodo itoi	1. Water Level				+			
	2. Oil Level							
Under the Hood	3. Belts & Hoses							
	4. Fluid Leaks							
Inside Vehicle	5. Floor Clean							
	6. Seats & Windows							
	7. Emergency Equipment							
Start Engine	8. Oil Pressure							
otart Engino	9. Air/Vacuum Pressure							
	10. Fuel Level							
	11. Heaters & Defrosters							
	12. Wipers & Washer							
	13. Service Door							
	14. Low & High Beam Indicator							
	15. Left Signal Indicator							
	16. Amber Warning Lights							
	17. Emergency Exit & Buzzer							
Outside Vehicle	18. Rear Clear Lights							
	19. Amber Warning Lights							
	20. Left Turn Signal, Rear							
	21. Brake & Taillights							
	22. I.D. Lights							
	23. Exhaust System							
	24. Tires & Wheels, Rear							
Move to Front	25. Headlights, High Beam							
	26. Clear Lights							
	27. Amber Warning Lights							
	28. Left Turn Signal, Front							
	29. Front Tires & Wheels							
	30. Crossover Mirror							
	31. Both Rear View Mirrors							
Re-Enter Vehicle	32. Low Beam Indicator							
	33. Right Signal Indicator							
	34. Red Warning Lights							
Outside Vehicle	35. Right Turn Signal, Front							
	36. Red Warning Lights							
Move to Front	37. Right Turn, Signal	1						
	38. Red Warning Lights	1						
Re-Enter Vehicle	39. Service Brakes	1						
	40. Parking Brake	1						
Odometer	Mon. Tues. Wed.	Thurs.	Fri.		Date:	L	<u> </u>	<u>.</u>
	mom raco. Wear				<u> </u>			

Odomete	r		Mon.	Tues.	Wed.	Thurs.	Fri.			Date:			
Regular	Before	Am						Activity	Before	Am			
Route	After	Pm						Trips	After	Pm			

Signature:	Provided by NDE

APPENDIX D

Nebraska State Statute Section 13-1208 R.R.S.:

Municipality, county, or qualified public-purpose organization; powers; municipality or county; contract with school district; conditions.(1) Any municipality, county, or qualified public-purpose organization may lease, purchase, construct, own, maintain, operate, or contract for the operation of public transportation, including special transportation for the elderly or handicapped, and apply for and accept advances, loans, grants, contributions, and any other form of assistance from the federal government, the state, or any public or private sources for the purpose of providing a public transportation system. Any special transportation system for the elderly or handicapped shall include transportation of necessary personal escorts of such elderly or handicapped riders. (2) Any municipality or county in providing public transportation for the elderly under subsection (1) of this section may contract with the school board or board of education of a public school district for the use of a school bus at times other than during the normal school day or on days when school is not in session if all costs incurred by such municipality or county are paid for with money generated from passenger fees or federal or state funds. The contract shall provide that such municipality or county shall be liable for costs of maintenance, operation, insurance, and other reasonable expenses incurred in the use of such bus. No district shall be liable for any damages to any person riding in a school bus under a contract entered into pursuant to this subsection unless such damage is proximately caused by the gross negligence of the district. No district shall be required to modify or alter any school bus because of a contract entered into pursuant to this subsection. Any municipality or county when using a school bus upon a highway under a contract entered into pursuant to this subsection shall cover or conceal all school bus markings on such bus as required by section 60-6,175. (3) Any municipality or county may contract with the school board or board of education of any public school district for the use of school buses for emergency evacuation of members of the public by qualified law enforcement personnel during emergency or crisis situations that pose a threat to the health, safety, or well-being of the individuals to be evacuated. The contract shall provide that such municipality or county shall be liable for the costs of maintenance, operation, insurance, and other reasonable expenses incurred in the use of such buses. No district shall be liable for any damages to any person riding in a school bus under a contract entered into pursuant to this subsection unless such damage is proximately caused by the gross negligence of the district. No district shall be required to modify or alter any school bus because of a contract entered into pursuant to this subsection.

Nebraska State Statute Section 60-6,175(6) R.R.S.:

School bus; safety requirements; use of stop signal arm; use of warning signal lights; violations; penalty. (1) Upon meeting or overtaking, from the front or rear, any school bus on which the yellow warning signal lights are flashing, the driver of a motor vehicle shall reduce the speed of such vehicle to not more than twenty-five miles per hour, shall bring such vehicle to a complete stop when the school bus is stopped, the stop signal arm is extended, and the flashing red signal lights are turned on, and shall remain stopped until the flashing red signal lights are turned off, the stop signal arm is retracted, and the school bus resumes motion. This section shall not apply to approaching traffic in the opposite direction on a divided highway or to

TITLE 92 CHAPTER 91

approaching traffic when there is displayed a sign as provided in subsection (7) of this section directing traffic to proceed. Any person violating this subsection shall be guilty of a Class IV misdemeanor, shall be fined five hundred dollars, and shall be accessed points on his or her motor vehicle operator's license pursuant to section 60-4,182. (2) Except as provided in subsection (8) of this section, the driver of any school bus, when stopping to receive or discharge pupils, shall turn on flashing yellow warning signal lights at a distance of not less than three hundred feet when inside the corporate limits of any city or village and not less than five hundred feet nor more than one thousand feet in any area outside the corporate limits of any city or village from the point where such pupils are to be received or discharged from the bus. At the point of receiving or discharging pupils, the bus driver shall bring the school bus to a stop, extend a stop signal arm, and turn on the flashing red signal lights. After receiving or discharging pupils, the bus driver shall turn off the flashing red signal lights, retract the stop signal arm, and then proceed on the route. (3)(a) Except as provided in subdivision (b) of this subsection, no school bus shall stop to load or unload pupils unless there is at least four hundred feet of clear vision in each direction of travel. (b) If four hundred feet of clear vision in each direction of travel is not possible as determined by the school district, a school bus may stop to load or unload pupils if there is proper signage installed indicating that a school bus stop is ahead. (4) All pupils shall be received and discharged from the right front entrance of every school bus. If such pupils must cross a roadway, the bus driver shall instruct such pupils to cross in front of the school bus and the bus driver shall keep such school bus halted with the flashing red signal lights turned on and the stop signal arm extended until such pupils have reached the opposite side of such roadway. (5) The driver of a vehicle upon a divided highway need not stop upon meeting or passing a school bus which is on a different roadway or when upon a freeway and such school bus is stopped in a loading zone which is a part of or adjacent to such highway and where pedestrians are not permitted to cross the roadway. (6) Every school bus shall bear upon the front and rear thereof plainly visible signs containing the words school bus in letters not less than eight inches high. (7) When a school bus is being operated upon a highway for purposes other than the actual transportation of children either to or from school or school-sponsored activities, all markings thereon indicating school bus shall be covered or concealed. The stop signal arm and system of flashing yellow warning signal lights and flashing red signal lights shall not be operable through the usual controls. (8) When a school bus is (a) parked in a designated school bus loading area which is out of the flow of traffic and which is adjacent to a school site or (b) parked on a roadway which possesses more than one lane of traffic flowing in the same direction and which is adjacent to a school site, the bus driver shall engage only the hazard warning flasher lights when receiving or discharging pupils if a school bus loading area warning sign is displayed. Such signs shall not be directly attached to any school bus but shall be free standing and placed at the rear of a parked school bus or line of parked school buses. No school district shall utilize a school bus loading area warning sign unless such sign complies with the requirements of section 60-6,176.

APPENDIX E

Code of Federal Regulations 49 CFR 567.7

[Code of Federal Regulations]
[Title 49, Volume 6]
[Revised as of October 1, 2006]
From the U.S. Government Printing Office via GPO Access
[CITE: 49CFR567.7]

[Page 189-190]

TITLE 49--TRANSPORTATION

CHAPTER V--NATIONAL HIGHWAY TRAFFIC
— SAFETY ADMINISTRATION, DEPARTMENT
— OF TRANSPORTATION

PART 567 CERTIFICATION

Sec. 567.7 Requirements for persons who alter certified vehicles.

- (a) With respect to the vehicle alterations it performs, an alterer:
- (1) Has a duty to determine continued conformity of the altered vehicle with applicable Federal motor vehicle safety, Bumper, and Theft Prevention standards, and
- (2) Assumes legal responsibility for all duties and liabilities for certification under the Vehicle Safety Act.
- (b) The vehicle manufacturer's certification label and any information labels shall remain affixed to the vehicle and the alterer shall affix to the vehicle an additional label in the manner and location specified in Sec.567.4, in a manner that does not obscure any previously applied labels, and containing the following information:
- (1) The statement: ``This vehicle was altered by (individual or corporate name) in month and year in which alterations were completed)and as altered it conforms to all applicable Federal Motor Vehicle Safety, Bumper and Theft Prevention Standards affected by the alteration and in effect in (month, year)." The second date shall be no earlier than the date of manufacture of the certified vehicle (as specified on the certification label), and no later than the date alterations were completed.
- (2) If the gross vehicle weight rating or any of the gross axle weight ratings of the Vehicle as altered are different from those shown on the original certification label, the modified values shall be provided in the form specified in Sec. 567.4(g)(3) and (4).
- (3) If the vehicle as altered has a different type classification from that shown on the original certification label, the type as modified shall be provided.

TITLE 92 CHAPTER 91

APPENDIX E (cont'd)

Code of Federal Regulations 49 CFR 567.3

PART 567 CERTIFICATION

Sec. 567.3 Definitions.

Altered vehicle means a completed vehicle previously certified in accordance with Sec. 567.4 or Sec. 567.5 that has been altered other than by the addition, substitution, or removal of readily attachable components, such as mirrors or tire and rim assemblies, or by minor finishing operations such as painting, before the first purchase of the vehicle other than for resale, in such a manner as may affect the conformity of the vehicle with one or more Federal Motor Vehicle Safety Standard(s) or the validity of the vehicle's stated weight ratings or vehicle type classification.

Alterer means a person who alters by addition, substitution, or removal of components (other than readily attachable components) a certified vehicle before the first purchase of the vehicle other than for resale.

PRE-SERVICE EVALUATION FORM "Behind the Wheel" Evaluation

The "Behind the Wheel" training and pre-service evaluation is a required part of the Level I Pupil Transportation Driver Training Program. The driver candidate must be evaluated by a driver holding a current pupil transportation vehicle operator's permit. It can be conducted at the local school district. (Title 92, NAC, Chapter 91, 003.03B1 003.02C1).

This evaluation will provide the Level I Instructor and/or employer with valuable information as to the candidates' skill deficiencies that may need to be addressed.

The attached evaluation form lists the individual criteria that must be successfully completed by each driver candidate. Three columns are provided for checking each criteria in the event that more than one attempt is necessary for successful performance.

<u>Verification of the completion of the Level 1 Training Instructional</u> Course can only be issued upon providing documentation of the successful completion of this pre-service evaluation.

Please note: If you are submitting this documentation after you have completed the Level 1 Course, please also provide the following and fax to 308-865-8257. Form must be submitted within six months of completion of the Level 1 Course

_evel Instructor:	
Level Class Location:	
Level Class Ending Date:	

Safety Center database

SCHOOL TRANSPORTATION MANEUVERS/ROAD TEST EXAMINER'S SUMMARY

School/Contractor Providing Transportation:	
Examiner's Name (print)	School Bus Permit #
Driver's name:	Driver's License #
Capacity of Vehicle in Test Drive:	
Circle type of vehicle driven: (BUS) (SMALL VEHICLE)	
As driving examiner, I have observed this driver to be student / passenger vehicle as a requirement	•
EXAMINER'S SIGNATURE:	Date of Observation:
Submit Upload the completed Examiner's Summary to the	e Level I Instructor or to the Nebraska

When complete, this Pre-Service Checklist is to be kept by the driving examiner or the employer of the driver.

This first page of the form should be submitted to the Level Instructor or NE Safety Center as a completion record and a requirement of Level 1 Certification.

INSTRUCTIONS:

Evaluate the performance of the driver for each item within all categories to be tested. Using the following codes, indicate the driver's performance in the appropriate column:

P = PASS N/I = NEEDS IMPROVEMENT F = FAIL

Evaluate the items as many times as are indicated whenever possible. The PASS, NEEDS IMPROVEMENT or FAILS spaces should be left blank only if the task described does not occur during the road test.

<u>NOTE</u>: A = Ahead; B = Behind; R = Right; L = Left

		г 1	T11.4	г o	T18.45	- 2
<u>INITIAL START</u>	P	E 1 N/I	P	<u> </u>	TIME	= 3 F
Pre-trip inspection		1 1/1		1 1/1	1	-
Positions or checks seat and mirrors, fastens lap belt						
Checks gear position, puts in neutral or park						
Disengages clutch						
Starts engine – pushes button or turns key, releases button, uses clutch						
Warms up engine without racing						
Checks instruments						
Observes conditions – traffic						
Releases holding brake						
Signals intent to pull out						
Waits if necessary						
Engages starting gear						
Drives about 50' – stops to check brakes						
Accelerates smoothly into traffic lane						
Moves to proper following distance						

DACKING / STDAIGHT		1E 1	TIN	1E 2	TIM	E 3
BACKING / STRAIGHT	Р	N/I	Р	N/I	Р	F
Stops bus in correct position to back						
Using mirrors, checks that way is clear to back						
Puts transmission in reverse						
Using mirrors, back slowly and smoothly in a						
straight line						
Stops at desired point without hitting markers						

	TIM	IE 1	TIN	IE 2	TIN	IE 3
LEFT TURN	P	N/I	P	N/I	P	F
Observes conditions – A, B, traffic and						
pedestrians						
Activates left signal, moves to left turn lane at						
safe distance from turn						
Re-activates left turn signal at not less than 100'						
from turn						
Reduces speed to safe level						
Observes conditions – A, B, L-R-L, traffic						
pedestrians; stops if necessary						
Obeys traffic signs/signals/officers						
Turns when there is clearance in lane he/she will						
enter						
Turns smoothly, at safe speed, into correct lane						
of side street clearing center line and other						
obstacles						
Deactivates left turn signal						
Observes conditions – A, B, traffic						
Activates right turn signal						
Moves to furthest right traffic lane						
Deactivates right turn signal						
Maintains proper following distance						

	TIM	IE 1	TIN	IE 2	TIN	ЛЕ 3
RIGHT TURN	P	N/I	Р	N/I	Р	F
Observes conditions – A, B, traffic and						
pedestrians						
Activates right turn signal at not less and 100'						
before turn						
Reduces speed to safe level						
Observes conditions- A, B, L-R-L, traffic						
pedestrians; stops if necessary						
Obeys traffic signs, signals and officers						
Turns when there is clearance in lane he/she will						
enter						
Turns smoothly, at safe speed, as far to left of						
side street as necessary to clear obstacles						
Returns to right traffic lane immediately						
Deactivates right turn signal						
Maintains proper following distance						

			1		TIME		
RAILROAD CROSSING	P TIM	IE 1 N/I	P	N/I	P	3 F	
Stops the bus approximately 15 feet from the crossing • Place transmission in "Park" – or if there is no "Park" shift point, place in "Neutral" & press down on the service brake or set the parking brake. Turns off noisy motors and fans Opens bus door • Open the service door and driver's window while	P	N/I	P	N/I	P	F	
the transmission is in "Park" or "Neutral." Looks L-R-L, listens for at least 5 seconds Listen & look both directions along the track for any approaching trains. Closes bus door If no train is approaching, place in a gear low							
enough to permit crossing the tracks without having to shift gears if driving a vehicle with manual transmission. Vehicles with automatic transmissions should be in "Drive". Observes conditions – A, B, L-R-L, for clearance on							
other side of tracks, train and traffic When safe, proceed across tracks without stopping							
Double track, train passing on near side; driver waits for 15 seconds before crossing tracks Deactivate hazard warning flasher lights after crossing							
 Iast rail. The entrance door must be closed by the time the bus is clear of the final track. 							

CUDVES	TIN	/IE 1	TIN	1E 2	TIME 3		
CURVES	Р	N/I	Р	N/I	Р	F	
Maintains proper following distance							
Observes conditions – A, B, traffic roadway							
Decelerates before curve, down shifts if							
necessary							
Maintains safe speed through curve,							
accelerating slightly							
Maintains correct position in lane							

INTERCECTIONS/CTDAIGHTAMAY	TIM	IE 1	TIM	IE 2	TIN	1E 3
INTERSECTIONS/STRAIGHTAWAY	Р	N/I	Р	N/I	Р	F
Approaches intersection at safe speed						
Maintains proper following distance						
Observes conditions – A, B, L-R-L, traffic and						
pedestrians						
Yields right-of-way to pedestrians						
Obeys traffic signs, signals, officers						
Stops completely at rural and blind intersections						
Before starting from stop, observes conditions –						
A, B, L-R-L						
Crosses intersections at safe speed, staying in						
lane						
Does not cross until there is clearance on other						
side of the intersection						

ши с	TIME 1 TIME 2					1E 3
HILLS	Р	N/I	Р	N/I	Р	N/I
Stopping and Starting						
Maintains proper following distance						
Applies brakes as needed						
Observes conditions – A, B, traffic						
Comes to full stop at safe distance from vehicle or						
intersection ahead						
Shifts to N, holding bus with foot on brake only						
Observes conditions; A, B, L-R-L						
Shifts to low gear						
Releases clutch to engage engine and						
accelerates						
Releases foot brake and slowly accelerates						
Maintains proper following distance						
Shifting, Accelerating, Decelerating						
Checks brakes before beginning ascent or						
descent						
Shifts to a low gear						
Maintains safe speed						
Uses brakes as needed						
Does not shift while on hill						

LOADING AND UNLOADING	TIN	1E 1	TIN	IE 2	TIME 3		
LOADING AND UNLOADING	Р	N/I	Р	N/I	Р	F	
Activates amber warning lights not less than 500' or							
more than 1,000' in a rural area							
Stops vehicle in the lane nearest the right side of							
the roadway at bus stop							
Deactivates amber flashing warning lamps							
Activates red flashing warning lamps; extends stop							
arm; places transmission in neutral; keeps foot on							
brake during							
loading and unloading procedure							
Deactivates warning lamps on leaving bus stop;							
retracts stop arm							
Loads or unloads pupils with at least 400' of clear							
vision in each direction							

SECURING THE BUS	TIN	TIM	1E 2	TIM	E 3	
	Р	N/I	Р	N/I	Р	F
Set parking brake						
Shift to a low gear						
Check instruments						
Turn off all accessories						
Turn off all ignition and remove key						
Does post-trip inspection						
Upon leaving bus, secure door						

Comments:

TITLE 92 CHAPTER 91

APPENDIX G

This document is provided as a suggested form-schools should adapt to suit the district's individual needs. Completed forms should be kept for your school records.

Do not submit this form to the Nebraska Department of Education.

POST ROUTE CHECK OF VEHICLE Minimum Requirements

Week of		
TTCCK OII		
Vehicle #		
Venicle II		

Drivers are to initial the appropriate box indicating the following Post Route Check of the vehicle has been completed:

- No students remain on the vehicle
- Damage due to vandalism
- Vehicle keys have been removed
- Vehicle is secured

	Su	nda	y	Mo	nday	<u>.</u>	Tue	Tuesday		Wednesday		Thursday			Friday			Saturday			
	AMA A	PIM	Other	A.M.A.	₩ d	Other	AMA	bly.	Other	A.P.4	₩ d	Other	AMA	PM	Other	AMA	≱	Other	AIM	PIM	Other
Driver Initials																					
Confirmed by																					
Notes																					

Post Trip inspection sheets should be submitted on a weekly basis to school administration.